

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Honeywell Solstice® N40 Refrigerant (R-448A)

MSDS Number : 000000017419

Product Use Description : Refrigerant

Manufacturer or supplier's details : Honeywell International Inc.
101 Columbia Road
Morristown, NJ 07962-1057

For more information call : 800-522-8001
+1-973-455-6300
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : **Medical: 1-800-498-5701 or +1-303-389-1414**
: **Transportation (CHEMTREC): 1-800-424-9300 or +1-703-527-3887**
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : Liquefied gas

Color : clear colourless

Odor : slight ether-like

Classification of the substance or mixture

Classification of the substance or mixture : Gases under pressure, Liquefied gas
Simple Asphyxiant

GHS Label elements, including precautionary statements

Honeywell Solstice® N40 Refrigerant (R-448A)

000000017419

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

Symbol(s)

:



Signal word

: Warning

Hazard statements

: Contains gas under pressure; may explode if heated.
May displace oxygen and cause rapid suffocation.

Precautionary statements

: **Prevention:**
Use personal protective equipment as required.**Storage:**

Protect from sunlight. Store in a well-ventilated place.

Hazards not otherwise
classified: May cause frostbite.
May cause cardiac arrhythmia.
May cause eye and skin irritation.**Carcinogenicity**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: Mixture

Chemical Name	CAS-No.	Concentration
Difluoromethane	75-10-5	26.00 %
Pentafluoroethane	354-33-6	26.00 %
1,1,1,2-Tetrafluoroethane	811-97-2	21.00 %

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	20.00 %
trans-1,3,3,3-Tetrafluoroprop-1-ene	29118-24-9	7.00 %

SECTION 4. FIRST AID MEASURES

- Inhalation : Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.
- Skin contact : After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.
- Ingestion : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.

Notes to physician

- Treatment : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-bitten areas as needed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : The product is not flammable.
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Use extinguishing measures that are appropriate to local

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

circumstances and the surrounding environment.

Specific hazards during firefighting

- : Contents under pressure.
 This product is not flammable at ambient temperatures and atmospheric pressure.
 However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.
 Container may rupture on heating.
 Cool closed containers exposed to fire with water spray.
 Do not allow run-off from fire fighting to enter drains or water courses.
 Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
 In case of fire hazardous decomposition products may be produced such as:
 Hydrogen halides
 Hydrogen fluoride
 Carbon monoxide
 Carbon dioxide (CO₂)
 Carbonyl halides

Special protective equipment for firefighters

- : In the event of fire and/or explosion do not breathe fumes.
 Wear self-contained breathing apparatus and protective suit.
 No unprotected exposed skin areas.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions

- : Immediately evacuate personnel to safe areas.
 Keep people away from and upwind of spill/leak.
 Wear personal protective equipment. Unprotected persons must be kept away.
 Remove all sources of ignition.
 Avoid skin contact with leaking liquid (danger of frostbite).
 Ventilate the area.
 After release, disperses into the air.
 Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
 Avoid accumulation of vapours in low areas.
 Unprotected personnel should not return until air has been tested and determined safe.
 Ensure that the oxygen content is $\geq 19.5\%$.

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

Environmental precautions : Prevent further leakage or spillage if safe to do so.
The product evaporates readily.

Methods for cleaning up : Ventilate the area.

SECTION 7. HANDLING AND STORAGE**Handling**

Handling : Handle with care.
Avoid inhalation of vapour or mist.
Do not get in eyes, on skin, or on clothing.
Wear personal protective equipment.
Use only in well-ventilated areas.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Follow all standard safety precautions for handling and use of compressed gas cylinders.
Use authorized cylinders only.
Protect cylinders from physical damage.
Do not puncture or drop cylinders, expose them to open flame or excessive heat.
Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
Do not remove screw cap until immediately ready for use.
Always replace cap after use.

Advice on protection against fire and explosion : The product is not flammable.
Can form a combustible mixture with air at pressures above atmospheric pressure.

Storage

Requirements for storage areas and containers : Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Storage rooms must be properly ventilated.
Ensure adequate ventilation, especially in confined areas.
Protect cylinders from physical damage.

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Protective measures : Do not breathe vapour.
Avoid contact with skin, eyes and clothing.
Ensure that eyewash stations and safety showers are close to the workstation location.
- Engineering measures : General room ventilation is adequate for storage and handling.
Perform filling operations only at stations with exhaust ventilation facilities.
- Eye protection : Wear as appropriate:
Safety glasses with side-shields
If splashes are likely to occur, wear:
Goggles or face shield, giving complete protection to eyes
- Hand protection : Leather gloves
In case of contact through splashing:
Protective gloves
Neoprene gloves
Polyvinyl alcohol or nitrile- butyl-rubber gloves
- Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).
Wear cold insulating gloves/ face shield/ eye protection.
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
Wear a positive-pressure supplied-air respirator.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Ensure adequate ventilation, especially in confined areas.
Avoid contact with skin, eyes and clothing.
Remove and wash contaminated clothing before re-use.
Keep working clothes separately.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis

Honeywell Solstice® N40 Refrigerant (R-448A)

000000017419

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

Difluoromethane	75-10-5	TWA : time weighted average	2,200 mg/m ³ (1,000 ppm)	2007	WEEL:US. AIHA Workplace Environmental Exposure Level (WEEL) Guides
Difluoromethane	75-10-5	TWA : time weighted average	(1,000 ppm)	1994	Honeywell:Limit established by Honeywell International Inc.
Pentafluoroethane	354-33-6	TWA : time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
1,1,1,2-Tetrafluoroethane	811-97-2	TWA : time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
1,1,1,2-Tetrafluoroethane	811-97-2	TWA : time weighted average	4,240 mg/m ³ (1,000 ppm)	2007	WEEL:US. AIHA Workplace Environmental Exposure Level (WEEL) Guides
2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	TWA : time weighted average	(500 ppm)	2009	WEEL:US. AIHA Workplace Environmental Exposure Level (WEEL) Guides
2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	TWA : time weighted average	(500 ppm)	03 15 2010	Honeywell:Limit established by Honeywell International Inc.

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	STEL : Short term exposure limit	(1,500 ppm)	03 15 2010	Honeywell:Limit established by Honeywell International Inc.
trans-1,3,3,3-Tetrafluoroprop-1-ene	29118-24-9	TWA : time weighted average	(800 ppm)	2012	WEEL:US. AIHA Workplace Environmental Exposure Level (WEEL) Guides
trans-1,3,3,3-Tetrafluoroprop-1-ene	29118-24-9	TWA : time weighted average	(800 ppm)	31.03.11	Honeywell:Limit established by Honeywell International Inc.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Liquefied gas
Color	: clear colourless
Odor	: slight ether-like
pH	: Note: neutral
Melting point/freezing point	: Note: no data available
Boiling point/boiling range	: Note: no data available
Flash point	: Note: Not applicable
Lower explosion limit	: Note: None

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

Upper explosion limit	: Note: None
Vapor pressure	: 1,120 kPa at 21.1 °C(70.0 °F) 2,588 kPa at 54.4 °C(129.9 °F)
Vapor density	: Note: no data available
Density	: Note: no data available
Water solubility	: Note: no data available
Partition coefficient: n-octanol/water	: Note: no data available
Ignition temperature	: Note: no data available
Decomposition temperature	: > 250 °C Note: To avoid thermal decomposition, do not overheat.

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Hazardous polymerisation does not occur.
Conditions to avoid	: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Decomposes under high temperature. Some risk may be expected of corrosive and toxic decomposition products. Can form a combustible mixture with air at pressures above atmospheric pressure.

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

Do not mix with oxygen or air above atmospheric pressure.

Incompatible materials to avoid : Potassium
Calcium
Powdered metals
Finely divided aluminium
Finely divided magnesium
Zinc

Hazardous decomposition products : Halogenated compounds
Hydrogen fluoride
Carbonyl halides
Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity
Difluoromethane : LC50: > 520000 ppm
Exposure time: 4 h
Species: Rat

Pentafluoroethane : > 769000 ppm
Exposure time: 4 h
Species: Rat

1,1,1,2-Tetrafluoroethane : LC50: > 500000 ppm
Exposure time: 4 h
Species: Rat

2,3,3,3-Tetrafluoroprop-1-ene : LC50: > 400000 ppm
Exposure time: 4 h
Species: Rat

trans-1,3,3,3-Tetrafluoroprop-1-ene : 100000 ppm
Species: Mouse
Note: Acute (4-Hour) Inhalation Toxicity Screening Study (mouse): No lethality at >100,000 ppm.

LC50: > 207000 ppm
Exposure time: 4 h
Species: Rat

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

Skin irritation
trans-1,3,3,3-
Tetrafluoroprop-1-ene

: Species: Rabbit
Result: No skin irritation
Method: OECD Test Guideline 404

Sensitisation
Difluoromethane

: Cardiac sensitization
Species: dogs
Note: No-observed-effect level
>350 000 ppm

Pentafluoroethane

: Cardiac sensitization
Species: dogs
Note: No-observed-effect level
75 000 ppm
Lowest observed effect level
100 000 ppm

1,1,1,2-Tetrafluoroethane

: Cardiac sensitization
Species: dogs
Note: No-observed-effect level
50 000 ppm
Lowest observed effect level
75 000 ppm

2,3,3,3-Tetrafluoroprop-1-
ene

: Cardiac sensitization
Species: dogs
Result: No effects observed for exposures up to 12% (120,189
ppm).

trans-1,3,3,3-
Tetrafluoroprop-1-ene

: Cardiac sensitization
Species: dogs
Note: Did not cause sensitisation on laboratory animals.

Repeated dose toxicity
Difluoromethane

: Species: Rat
Application Route: Inhalation
Exposure time: (90 d)
NOEL: 50000 ppm
Subchronic toxicity

Pentafluoroethane

: Species: Rat

Honeywell Solstice® N40 Refrigerant (R-448A)

000000017419

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

	Application Route: Inhalation Exposure time: (4 Weeks) NOEL: 50000 ppm Subchronic toxicity
1,1,1,2-Tetrafluoroethane	: Species: Rat NOEL: 40000 ppm
2,3,3,3-Tetrafluoroprop-1-ene	: Species: Rat Application Route: Inhalation Exposure time: (2 Weeks) NOEL: 50000 ppm
	Species: Rat Application Route: Inhalation Exposure time: (4 Weeks) NOAEL (No observed adverse effect level): 50000 ppm
	Species: Rat Application Route: Inhalation Exposure time: (13 Weeks) NOAEL (No observed adverse effect level): 50000 ppm
	Species: Rabbit, male Application Route: Inhalation Exposure time: (28 d) No-observed-effect level: 500 ppm
	Species: Rabbit, female Application Route: Inhalation Exposure time: (28 d) No-observed-effect level: 1000 ppm
	Species: Mini-pig Application Route: Inhalation Exposure time: (28 d) NOAEL (No observed adverse effect level): 10,000 ppm highest exposure tested
trans-1,3,3,3-Tetrafluoroprop-1-ene	: Species: Rat Application Route: Inhalation Exposure time: (13 Weeks) NOEL: 5000 ppm Causes mild effects on the heart.

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

- Genotoxicity in vitro
- Difluoromethane : Test Method: Ames test
Result: negative
- Pentafluoroethane : Test Method: Ames test
Result: negative
- 1,1,1,2-Tetrafluoroethane : Note: In vitro tests did not show mutagenic effects
- 2,3,3,3-Tetrafluoroprop-1-ene : Test Method: Ames test
Result: 20% and higher, positive in TA 100 and e. coli WP2 uvrA, negative in TA98, TA100, and TA1535.
- trans-1,3,3,3-Tetrafluoroprop-1-ene : Test Method: Chromosome aberration test in vitro
Cell type: Human lymphocytes
Result: negative
- : Cell type: Human lymphocytes
Result: negative
Method: Mutagenicity (in vitro mammalian cytogenetic test)
- : Test Method: Chromosome aberration test in vitro
Result: negative
- : Cell type: Human lymphocytes
Result: negative
- : Cell type: Chinese Hamster Ovary Cells
Result: negative
- : Test Method: Chromosome aberration test in vitro
Cell type: Human lymphocytes
Result: negative
Note: Dose 760,000 ppm
- : Test Method: Chromosome aberration test in vitro
Cell type: Chinese Hamster Lung Cells
Result: negative
- : Test Method: Ames test
Result: negative

Genotoxicity in vivo

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

Difluoromethane	:	Species: Mouse Cell type: Bone marrow Method: Mutagenicity (micronucleus test) Result: negative
2,3,3,3-Tetrafluoroprop-1-ene	:	Species: Mouse Cell type: Micronucleus Dose: up to 200,000 ppm (4 hour) Result: negative
	:	Test Method: Unscheduled DNA synthesis Dose: up to 50,000 ppm (4 weeks) Result: negative
	:	Species: Rat Cell type: Micronucleus Dose: up to 50,000 ppm (4 weeks) Result: negative
trans-1,3,3,3-Tetrafluoroprop-1-ene	:	Test Method: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Mouse Cell type: Micronucleus Application Route: Inhalation Result: negative
Reproductive toxicity 2,3,3,3-Tetrafluoroprop-1-ene	:	Species: Rat Application Route: Inhalation exposure Exposure time: Two-generation reproductive toxicity NOAEL,parent: 50,000 ppm NOAEL,F1: 50,000 ppm NOAEL,F2: 50,000 ppm
Teratogenicity Difluoromethane	:	Species: Rat Dose: NOEL - 50,000 ppm Note: Did not show teratogenic effects in animal experiments. Species: Rabbit Dose: NOEL - 50,000 ppm

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

Note: Did not show teratogenic effects in animal experiments.

Pentafluoroethane : Species: Rabbit
Application Route: Inhalation exposure
NOAEL, Teratog: 50,000 ppm
NOAEL, Maternal: 50,000 ppm
Note: Did not show teratogenic effects in animal experiments.

Species: Rat
Application Route: Inhalation exposure
NOAEL, Teratog: 50,000 ppm
NOAEL, Maternal: 50,000 ppm
Note: Did not show teratogenic effects in animal experiments.

2,3,3,3-Tetrafluoroprop-1-ene : Species: Rat
Dose: NOAEL (No observed adverse effect level) - 50,000 ppm

Species: Rabbit
Dose: NOAEL (No observed adverse effect level) - 4,000 ppm

trans-1,3,3,3-Tetrafluoroprop-1-ene : Species: Rabbit
Method: Prenatal Developmental Inhalation Toxicity Study
Note: Did not show teratogenic effects in animal experiments.

Species: Rat
Method: Prenatal Developmental Inhalation Toxicity Study
Note: Did not show teratogenic effects in animal experiments.

Further information
1,1,1,2-Tetrafluoroethane : Note:
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Rapid evaporation of the liquid may cause frostbite.
Avoid skin contact with leaking liquid (danger of frostbite).

SECTION 12. ECOLOGICAL INFORMATION

Toxicity to fish
2,3,3,3-Tetrafluoroprop-1-ene : LC50: > 197 mg/l
Exposure time: 96 h

Honeywell Solstice® N40 Refrigerant (R-448A)

000000017419

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

Species: Cyprinus carpio (Carp)
Method: OECD Test Guideline 203
Note: No demonstrable toxic effect in saturated solution.

trans-1,3,3,3-
Tetrafluoroprop-1-ene : NOEC: > 117 mg/l
Exposure time: 96 h
Species: Cyprinus carpio (Carp)

Toxicity to daphnia and other aquatic invertebrates
2,3,3,3-Tetrafluoroprop-1-ene : EC50: > 83 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 202

trans-1,3,3,3-
Tetrafluoroprop-1-ene : EC50: > 160 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)

Toxicity to algae
2,3,3,3-Tetrafluoroprop-1-ene : EC50: > 100 mg/l
Species: Scenedesmus capricornutum (fresh water algae)

trans-1,3,3,3-
Tetrafluoroprop-1-ene : Growth inhibition
NOEC: > 170 mg/l
Exposure time: 72 h
Species: Algae

Biodegradability
Difluoromethane : Note: Minimal

Pentafluoroethane : Result: Not readily biodegradable.
Value: 5 %
Method: OECD 301 D

2,3,3,3-Tetrafluoroprop-1-ene : Result: Not readily biodegradable.

trans-1,3,3,3-
Tetrafluoroprop-1-ene : aerobic
Result: Not readily biodegradable.

Further information on ecology

Additional ecological : This product is subject to U.S. Environmental Protection

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

information

Agency Clean Air Act Regulations at 40 CFR Part 82.
 This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 3163
 Proper shipping name : LIQUEFIED GAS, N.O.S.
 (Pentafluoroethane, Difluoromethane, 1,1,1,2-Tetrafluoroethane)
 Class : 2.2
 Packing group :
 Hazard Labels : 2.2

IATA UN/ID No. : UN 3163
 Description of the goods : LIQUEFIED GAS, N.O.S.
 (Pentafluoroethane, Difluoromethane, 1,1,1,2-Tetrafluoroethane)
 Class : 2.2
 Hazard Labels : 2.2
 Packing instruction (cargo aircraft) : 200
 Packing instruction (passenger aircraft) : 200

IMDG UN/ID No. : UN 3163
 Description of the goods : LIQUEFIED GAS, N.O.S.
 (PENTAFLUOROETHANE, DIFLUOROMETHANE, 1,1,1,2-TETRAFLUOROETHANE)
 Class : 2.2
 Hazard Labels : 2.2
 EmS Number : F-C, S-V

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**Inventories**

- US. Toxic Substances Control Act : On TSCA Inventory
- Australia. Industrial Chemical (Notification and Assessment) Act : Not in compliance with the inventory
- Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL.
- Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory
- Korea. Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory
- Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act : Not in compliance with the inventory
- China. Inventory of Existing Chemical Substances : Not in compliance with the inventory
- New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand : Not in compliance with the inventory
- TSCA 12B : US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)
- 2,3,3,3-Tetrafluoroprop-1-ene 754-12-1

National regulatory information

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

- SARA 302 Components** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
- SARA 313 Components** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
- SARA 311/312 Hazards** : Sudden Release of Pressure Hazard
Acute Health Hazard
- California Prop. 65** : WARNING! This product contains a chemical known to the State of California to cause cancer.
Dichloromethane 75-09-2
- : WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
Chloromethane 74-87-3
- Massachusetts RTK** : Dichloromethane 75-09-2
- Pennsylvania RTK** : Difluoromethane 75-10-5
- WHMIS Classification** : A: Compressed Gas
This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16. OTHER INFORMATION

Honeywell Solstice® N40 Refrigerant (R-448A)**000000017419**

Version 1.4

Revision Date 10/30/2014

Print Date 12/22/2014

	HMIS III	NFPA
Health hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 04/29/2014

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group